

1. Product Name: POWER PLUS X71

2. Physical and Chemical Properties

Appearance	: Clear, Orange Liquid
Specific Gravity	: 1.035 - 1.045
Odour	: Sassafras
pH	: 11.3 – 12.3
Shelf Life	: One Year in original unopened containers

3. <u>Hazard Identification</u> <u>Rating Scale:</u>

- 0 = Minimal
- 1 =Slight
- 2 = Moderate
- 3 =Serious
- 4 =Severe



4. Occupational Exposure Limits (Hazardous Ingredients)

Material	Long Term – 8Hr. TWA		Short Term – 10mins. TWA	
	ppm	mg.m ³	ppm	mg.m ³
2-Butoxyethanol	50			
Isopropyl Alcohol	400			

Dated: January 2023

5. Health Hazard

Area	Effects of Over	First Aid Procedure
	Exposure	
Skin	Prolonged or repeated	Wash affected area with
	skin contact may cause	water. Launder clothing
	temporary irritation.	before reuse.
Eyes	Contact can cause	Irrigate with large amounts of
	irritation and possibly	running water, lifting upper
	redness.	and lower lids for at least 15-
		20 mins. If pain or irritation
		occurs, seek medical
		attention immediately.
Inhalation	Excessive inhalation of	Move patient to fresh air. Get
	vapours can cause nasal	medical attention if
	and respiratory tract	respiratory irritation persists.
	irritation.	
Ingestion	May cause nausea,	Give several glasses of water.
	headache, drowsiness,	Get medical attention.
	dizziness, depending on	
	quantity ingested.	

6. Fire Hazard

This product is classified as Flash Point (°C) Extinguishing Media

Conditions to Avoid Decomposition Products

Special Fire Fighting Procedures

- : Non-Flammable
- : N/A
- : Non-Flammable, will not act as a fuel to fire No special procedures required.
- : None required
- : Minimal hydrocarbons, hazardous polymerization will not occur
- : None directly related to this product



7. Personal Protection

Respirator	: Not normally required during normal use and handling. In enclosed areas, an approved respirator should be worn by persons sensitive			
	to cleaning compounds. Type Ori-nasal or OSHA equivalent.			
Skin	: For all cleaning compounds wear protective gloves. (Nitrile, rubber or vinyl)			
Eyes	:Wear chemical splash goggles.			
Other	:Wear impervious clothing or boots.			

7. <u>Handling & Storage</u> Precautionary Measures

Ventilation

8. <u>Transport</u> Packing group

9. Biodegradable

10.Spillage / Disposal Method

: No special handling procedures.

: Local exhaust ventilation should be adequate when used in confined areas.

: N/A

Readily decomposed.

Spill:- Stop leaks and contain spill.
Reclaim if possible or dilute with large amounts of water.
Disposal:- Local Waste Disposal Authority.

12. DISCLAIMER

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION. SELLER ASSUMES NO RESPONSIBILITY FOR INJURY TO BUYER OR THIRD PERSONS CAUSED BY THE MATERIAL IF PROPER SAFETY PROCEDURES ARE NOT ADHERED TO OR IF ABNORMAL USE IS MADE OF THE MATERIAL. IN NO EVENT WILL SELLER BE LIAIBLE FOR ACCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF THIS MATERIAL.

SCL Products are guaranteed against defective materials and manufacture and are sold subject to its Standard Terms & Conditions of Sale, copies of which may be obtained on request. Whilst SCL endeavours to ensure that any advice, recommendations, specifications or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.