

1. Product Name : KICKER

2. Physical and Chemical Properties

: Clear Lilac Liquid
 Odor : Mild Solvent
 Specific Gravity : 1.045 - 1.055 @ 28 °C
 pH (10%) : 11.5 - 12.5
 Shelf Life : One year in original, unopened containers.

3. Composition

	<u>CAS NO.</u>
Detergent Builders	N/A
2-Butoxyethanol	111-76-2
Isopropyl Alcohol	67-63-0
Sodium Hydroxide, 50%	1310-73-2

4. Occupational Exposure Limits (Hazardous Ingredients)

Material	Long Term -8 Hr.		Treshold Limit Value	
	TWA		CL	
	ppm	mg.m3	ppm	mg.m3
2 - Butoxyethanol	25- skin		Not Listed	
Sodium Hydroxide			2	
Isopropyl Alcohol	400		Not Listed	

5. Health Hazard

Area	Effects of Over Exposure	First Aid Procedure
Skin	Irritant	Wash exposed area with water. Launder clothing before reuse.
Eyes	Can cause severe irritation, possible corneal injury	Irrigate with water for 15 mins. Lifting upper and lower lids. If pain and/or irritation persists seek medical attention.
Inhalation	Excessive inhalation of vapors can cause nasal and respiratory tract irritation.	Move patient to fresh air, if breathing is difficult, administer oxygen. Get medical attention.
Ingestion	Harmful if swallowed, may cause nausea, headache, drowsiness, dizziness, depending on quantity ingested	Give two glasses of water and induct vomiting. Never give anything to an unconscious person. Get medical attention.

Revision #06 | Dated: January 2023



6. Fire Hazard

This Product is classified as : Non-Flammable Food Processing
Flash Point (oC) : Cleaner / Degreaser Cleaner
Extinguishing Media : Carbon Dioxide, Dry Chemical, Water Fog, Foam
Conditions to Avoid : Do not mix with acids
Decomposition Products : Various Hydrocarbons
Special Fire Fighting Procedures : Wear protective boots, suites, gloves, face shield, Hard hat, NIOSH approved self-contained breathing apparatus.

7. Handling & Storage

Precautionary Measures : Store away from Oxidizing agents
Ventilation : Good ventilation should be provided in enclosed areas. Local exhaust ventilation should be used to maintain tolerant levels of exposure.

Personal Protection

Respirator : In enclosed areas an approved respirator should be Worn by persons sensitive to solvent fumes.
Type " Ori -nasal_ or OSHA equivalent
:Wear protective gloves (Nitrile rubber or vinyl)
:Wear chemicals splash goggles

8. Transport

Packing group : N/A
UN/ SI Number : N/A
UN/ Hazard Class :N/A

9. Spillage / Disposal method

Spill : Contain spill, reclaim if possible or dilute with large Amounts of water
Disposal : Local waste disposal authority.

10. DISCLAIMER

TO THE BEST OF OUR KNOWLEDGE , THE INFORMATION CONTAINED HEREIN IS ACCURATE. NO WARRANTY IS EX PRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION. SELLER ASSUMES NO RESPONSIBILITY FOR INJURY TO BUYER OR THIRD PERSONS CAUSED BY THE MATERIAL IF PROPER SAFETY PROCEDURES ARE NOT ADHERED TO OR IF ABNORMAL USE IS MADE OF THE MATERIAL. IN NO EVENT WILL SELLER BE LIABLE FOR ACCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF THIS MATERIAL.

SCL products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms & Conditions of Sale,copies of which may be obtained on request. Whilst SCL endeavors to ensure that any advice ,recommendations,specification or information it may give is accurate and correct,it cannot because it has no direct or continuous control over where or how its products are applied,accept any liability either directly or indirectly arising from the use of its products,whether or not in accordance with any advice,specification,recommendation or information given by it.